

268 Model



GVW (lbs.) 26,000
AXLE CAPACITY (lbs.) Front 10,000 / Rear 19,000
SPRING CAPACITY (lbs.) Front 12,000 / Rear 19,000
ENGINE (Hino) JO8E-TV Diesel 6-cyl. in-line, turbo intercooled
MAX. OUTPUT (HP) 220 @ 2,500 rpm
MAX. TORQUE (lb.ft) 520 @ 1,500 rpm
TRANSMISSION
 Standard 6-speed Eaton FS5406A
 Automatic (Opt.) 6-speed Allison 2200 RDS
SERVICE BRAKES Hydraulic disc front and rear
WHEELS 22.5 inch x 8.25 inch, 10 stud disc
TIRE SIZE 11R22.5

WHEELBASE CODES*

	M	P	R	T	V
WB	205.0	217.0	235.0	253.0	271.0
CA	137.6	149.6	167.6	185.6	203.6

338 Model



GVW (lbs.) 33,000
AXLE CAPACITY (lbs.) Front 12,000 / Rear 21,000
SPRING CAPACITY (lbs.) Front 12,000 / Rear 21,000
ENGINE (Hino) JO8E-TV Diesel 6-cyl. in-line, turbo intercooled
MAX. OUTPUT (HP) 220 @ 2,500 rpm
MAX. TORQUE (lb.ft) 520 @ 1,500 rpm
TRANSMISSION
 Standard 6-speed Eaton FS5406A
 Automatic (Opt.) 6-speed Allison 2500 RDS
SERVICE BRAKES Hydraulic disc front and rear
WHEELS 22.5 inch x 8.25 inch, 10 stud disc
TIRE SIZE 11R22.5

WHEELBASE CODES*

	R	T	V
WB	235.0	253.0	271.0
CA	167.6	185.6	203.6

358 Model



GVW (lbs.) 35,000
AXLE CAPACITY (lbs.) Front 12,000 / Rear 23,000
SPRING CAPACITY (lbs.) Front 12,000 / Rear 23,000
ENGINE (Hino) JO8E-TW Diesel 6-cyl. in-line, turbo intercooled
MAX. OUTPUT (HP) 260 @ 2,500 rpm
MAX. TORQUE (lb.ft) 585 @ 1,500 rpm
TRANSMISSION
 Standard 6-speed Eaton FS6406A
 Automatic (Opt.) 6-speed Allison 3000 RDS
SERVICE BRAKES Full air
WHEELS 22.5 inch x 8.25 inch, 10 stud disc
TIRE SIZE 11R22.5

WHEELBASE CODES**

	L	M	T	V
WB	187.0	205.0	253.0	271.0
CA	119.6	137.6	185.6	203.6

WB: Distance between the centerline and the front and rear axles
 CA: Distance from the back of the cab to the centerline of the rear axle

HINO



2010 Model Year

www.hinocanada.com

155 Model



GVW (lbs.) 14,700
AXLE CAPACITY (lbs.) Front 6,850 / Rear 11,250
SPRING CAPACITY (lbs.) Front 6,850 / Rear 12,600
ENGINE (Hino) JO5D-TF Diesel, 4-cyl. in-line, turbo intercooled
MAX. OUTPUT (HP) 175 @ 2,500 rpm
MAX. TORQUE (lb.ft) 376 @ 1,600 rpm
TRANSMISSION Standard 4-speed automatic Aisin 450-43LE
SERVICE BRAKES Hydraulic disc front and rear
WHEELS 16 inch x 5.5K-122, 6 stud disc
TIRE SIZE 215/85R16

WHEELBASE CODES**

	1	2	3	4
WB	110.6	135.0	152.4	165.4
CA	87.5	111.9	129.2	142.2

165 Model



GVW (lbs.) 16,000
AXLE CAPACITY (lbs.) Front 6,250 / Rear 11,000
SPRING CAPACITY (lbs.) Front 6,000 / Rear 12,000
ENGINE (Hino) JO5D-TF Diesel, 4-cyl. in-line, turbo intercooled
MAX. OUTPUT (HP) 175 @ 2,500 rpm
MAX. TORQUE (lb.ft) 376 @ 1,600 rpm
TRANSMISSION Standard 5-speed Eaton FS4205A
 Automatic (Opt.) 6-speed Allison 1000 RDS
 Automatic (Opt.) 4-speed Aisin 450-43LE
SERVICE BRAKES Hydraulic disc front and rear
WHEELS 19.5 inch x 6.00RW inch, 8 stud disc
TIRE SIZE 225/70R19.5

WHEELBASE CODES*

	K	M
WB	183.0	201.0
CA	119.6	137.6

185 Model



GVW (lbs.) Eaton / Allison 18,000 / Aisin 17,600
AXLE CAPACITY (lbs.) Front 6,250 / Rear 13,000
SPRING CAPACITY (lbs.) Front 6,000 / Rear 13,000
ENGINE (Hino) JO5D-TF Diesel, 4-cyl. in-line, turbo intercooled
MAX. OUTPUT (HP) 175 @ 2,500 rpm
MAX. TORQUE (lb.ft) 376 @ 1,600 rpm
TRANSMISSION Standard 5-speed Eaton FS4205A
 Automatic (Opt.) 6-speed Allison 1000 RDS
 Automatic (Opt.) 4-speed Aisin 450-43LE
SERVICE BRAKES Hydraulic disc front and rear
WHEELS 19.5 inch x 6.00RW inch, 8 stud disc
TIRE SIZE 225/70R19.5

WHEELBASE CODES*

	J	K	M
WB	169.0	183.0	201.0
CA	105.6	119.6	137.6

258 Model



GVW (lbs.) 25,500
AXLE CAPACITY (lbs.) Front 8,000 / Rear 17,500
SPRING CAPACITY (lbs.) Front 8,000 / Rear 19,000
ENGINE (Hino) JO8E-TV Diesel 6-cyl. in-line, turbo intercooled
MAX. OUTPUT (HP) 220 @ 2,500 rpm
MAX. TORQUE (lb.ft) 520 @ 1,500 rpm
TRANSMISSION Standard 6-speed Eaton FS5406A
 Automatic (Opt.) 6-speed Allison 2200 RDS
SERVICE BRAKES Hydraulic disc front and rear
WHEELS 19.5 inch x 6.75RW inch, 8 stud disc
TIRE SIZE 245/70R19.5

WHEELBASE CODES*

	J	L	M	P	R	T
WB	175.0	187.0	205.0	217.0	235.0	253.0
CA	107.6	119.6	137.6	149.6	167.6	185.6

*See dealer for wheelbase / transmission availability
 **See dealer for wheelbase availability