



2020 MODEL YEAR CAB-OVER ENGINE AND CONVENTIONAL TRUCKS





CONTENTS

Model 155	4
Model 165	6
Model 195	8
Model 195 Crew Cab	10
Model 195h	12
Cab-over engine model trucks warranty coverage	14
Model 258	16
Model 268	18
Model 338	20
Model 358	22
Conventional model trucks warranty coverage	24
Hino Premium Protection	26



GVWR (lbs./kg)

Gross axle weight rating

(GAWR) (lbs./kg)

Engine (Hino)

Exhaust gas aftertreatment system

Max. Output (HP)

Max. Torque (lb.-ft.)

Transmission

Service brakes

Tire size

Wheelbase/CA*

WB 114.2 137.8 149.6

CA 92.2 115.8 127.6

14,500 / 6,580

Front 5,950 / 2,700

Front 5,510 / 2,500 (For 114.2" wheelbase)

Rear 9,880 / 4,480

J05E-TP 4-cylinder, 5.1 litre turbo diesel

DEF-SCR Dosing system

210 @ 2,500 rpm

440 @ 1,500 rpm

6-speed Aisin A465 O/D with lock-up

torque converter

Hydraulic / Vacuum assisted disc brakes with ABS

and Electronic Brake Force Distribution

215/75R17.5

Note: For a complete list of standard and optional features, visit your local Hino truck dealer.

**WB: Distance between the centerline of the front and rear axles*

CA: Distance from the back of the cab to the centerline of the rear axle



Model 155



GVWR (lbs./kg)
Gross axle weight rating
(GAWR) (lbs./kg)

16,000 / 7,257
Front 7,270 / 3,300
Rear 13,660 / 6,200

Engine (Hino)
Exhaust gas aftertreatment system

J05E-TP 4-cylinder, 5.1 litre turbo diesel
DEF-SCR Dosing system

Max. Output (HP)
Max. Torque (lb.-ft.)

210 @ 2,500 rpm
440 @ 1,500 rpm

Transmission

6-speed Aisin A465 O/D with lock-up
torque converter

Service brakes

Hydraulic disc brakes with ABS and
Electronic Brake Force Distribution

Tire size

225/70R19.5

Wheelbase/CA*

WB	114.2	137.8	149.6
CA	92.2	115.8	127.6

Note: For a complete list of standard and optional features, visit your local Hino truck dealer.
**WB: Distance between the centerline of the front and rear axles*
CA: Distance from the back of the cab to the centerline of the rear axle



*Models 165/195 available
with **Air Suspension** option
(Excluding 114.2" wheelbase)
Truck shown with optional equipment.*



Model 195 available with
limited slip differential option

Truck shown with optional equipment.



GVWR (lbs./kg)						
Gross axle weight rating (GAWR) (lbs./kg)						
Engine (Hino)						
Exhaust gas aftertreatment system						
Max. Output (HP)						
Max. Torque (lb.-ft.)						
Transmission						
Service brakes						
Tire size						
Wheelbase/CA*						
WB	114.2	137.8	149.6	161.4	173.2	185.0
CA	92.2	115.8	127.6	139.4	151.3	163.1

19,500 / 8,850
Front 7,270 / 3,300
Rear 13,660 / 6,200
J05E-TP 4-cylinder, 5.1 litre turbo diesel
DEF-SCR Dosing system
210 @ 2,500 rpm
440 @ 1,500 rpm
6-speed Aisin A465 O/D with lock-up torque converter
Hydraulic disc brakes with ABS and Electronic Brake Force Distribution
225/70R19.5

Note: For a complete list of standard and optional features, visit your local Hino truck dealer.
** WB: Distance between the centerline of the front and rear axles*
CA: Distance from the back of the cab to the centerline of the rear axle



Model 195



GVWR (lbs./kg)

Gross axle weight rating

(GAWR) (lbs./kg)

Engine (Hino)

Exhaust gas aftertreatment system

Max. Output (HP)

Max. Torque (lb.-ft.)

Transmission

Service brakes

Tire size

Wheelbase/CA*

WB 149.6 173.2

CA 87.9 111.5

19,500 / 8,850

Front 7,270 / 3,300

Rear 13,660 / 6,200

J05E-TP 4-cylinder, 5.1 litre turbo diesel

DEF-SCR Dosing system

210 @ 2,500 rpm

440 @ 1,500 rpm

6-speed Aisin A465 O/D with lock-up
torque converter

Hydraulic disc brakes with ABS and
Electronic Brake Force Distribution

225/70R19.5

Note: For a complete list of standard and optional features, visit your local Hino truck dealer.

** WB: Distance between the centerline of the front and rear axles*

CA: Distance from the back of the cab to the centerline of the rear axle



Truck shown with optional equipment.

*Model 195 Crew Cab available with
limited slip differential option*



Model 195h available with limited slip differential option
 Truck shown with optional equipment.



GVWR (lbs./kg)
 Gross axle weight rating (GAWR) (lbs./kg)

Engine (Hino)
 Exhaust gas aftertreatment system

Max. Output (HP)
 Max. Torque (lb.-ft.)

Transmission

Service brakes

Tire size

Wheelbase/CA*
 WB 137.8 149.6 173.2
 CA 115.8 127.6 151.3

19,500 / 8,850
 Front 7,270 / 3,300
 Rear 13,660 / 6,200

J05E-UG 4-cylinder, 5.1 litre turbo diesel
 DEF-SCR Dosing system

210 @ 2,500 rpm
 440 @ 1,500 rpm

6-speed Aisin A465 O/D with lock-up torque converter

Hydraulic disc brakes with ABS and Electronic Brake Force Distribution
 225/70R19.5

Note: For a complete list of standard and optional features, visit your local Hino truck dealer.
 * WB: Distance between the centerline of the front and rear axles
 CA: Distance from the back of the cab to the centerline of the rear axle



WARRANTY COVERAGE

Cab-Over Engine Model Trucks

Description

Months/ Mileage (km)

BASIC TRUCK COMPONENTS

Provides warranty protection against defects in material and workmanship for 36 months/ unlimited mileage. Includes towing* to the nearest Hino Dealer for warrantable failures. (Adjustments and expendables such as bulbs and fuses are covered for 90 days/ 5,000 km. Batteries and radio are covered for 12 months).

** To a maximum of \$1000 per tow*

36 months/ Unlimited

EXTENDED ENGINE

Provides warranty protection against defects in material and workmanship for 60 months/ 320,000 km for the J05 series engine internal components*, plus the following: the engine fuel injectors, fuel supply pump, and turbocharger.

** Excludes gaskets, oil seals and o-rings after expiration of the basic warranty period.*

60 months/ 320,000km

AUTOMATIC TRANSMISSION: AISIN A465

Warranty covers repair or replacement to correct any transmission malfunction resulting from defects in materials or workmanship for 60 months/ 320,000 km.

** Excludes seals, external gaskets after expiration of the basic warranty period, and excludes attaching equipment.*

60 months/ 320,000km

Description

Months/ Mileage (km)

REAR AXLE

Provides warranty protection against defects in material or workmanship for 60 months/ 320,000 km, whichever occurs first.

** Excludes oil seals, bearings and wheel end components after expiration of the 36 Month Basic Vehicle Coverage.*

60 months/ 320,000km

FRAME RAILS AND CROSS MEMBERS

Provides warranty protection against structural cracks in the frame caused by defects in material and workmanship for 60 months/ unlimited mileage.

60 months/ Unlimited

CAB

Provides warranty protection against corrosion perforation of the cab structure for 60 months/ unlimited mileage.

60 months/ Unlimited

EMISSIONS WARRANTY

Provides warranty protection for the emission control system against defects in material and workmanship for 60 months/ 160,000 km, whichever occurs first.

60 months/ 160,000km





GVWR (lbs./kg)	25,500 / 11,570
Gross axle weight rating (GAWR) (lbs./kg)	Front 8,000 / 3,630 Rear 17,500 / 7,940
Engine (Hino)	J08E-WU Diesel, 6-cylinder, turbo intercooled, 7.7L DEF-SCR Dosing system
Exhaust gas aftertreatment system	
Max. Output (HP)	230 @ 2,500 rpm
Max. Torque (lb.-ft.)	520 @ 1,500 rpm
Transmission	6-speed Allison 2200 RDS
Fuel tank (ltr./gal.)	189 / 50, aluminum (standard) 189 / 50 x 2 (optional)
Service brakes*	Hydraulic disc front and rear
Wheels	19.5 inch x 6.75 inch, 8 stud disc
Tire size	245/70R19.5
Wheelbase/CA**	
WB	175.0 187.0 205.0 217.0 235.0 253.0 271.0
CA	107.6 119.6 137.6 149.6 167.6 185.6 203.6



Model 258

Also available with 260HP

Truck shown with optional equipment.

* 258 models are also available with air brakes. See dealer for details.
 ** See dealer for wheelbase availability
 WB: Distance between the centerline of the front and rear axles.
 CA: Distance from the back of the cab to the centerline of the rear axle.



GVWR (lbs./kg)	25,950/ 11,771
Gross axle weight rating (GAWR) (lbs./kg)	Front 10,000 / 4,540 Rear 19,000 / 8,620
Engine (Hino)	J08E-WU Diesel, 6-cylinder, turbo intercooled, 7.7L
Exhaust gas aftertreatment system	DEF-SCR Dosing system
Max. Output (HP)	230 @ 2,500 rpm
Max. Torque (lb.-ft.)	520 @ 1,500 rpm
Transmission	6-speed Allison 2200 RDS
Fuel tank (ltr./gal.)	189 / 50, aluminum (standard)
Dual aluminum tank	189 / 50 x 2 (optional)
Service brakes	Hydraulic disc front and rear
Wheels	22.5 inch x 8.25 inch, 10 stud disc
Tire size	11R22.5
Wheelbase/CA*	
WB	175.0 187.0 205.0 217.0 235.0 253.0 271.0
CA	107.6 119.6 137.6 149.6 167.6 185.6 203.6



.....

** See dealer for wheelbase availability*
WB: Distance between the centerline of the front and rear axles.
CA: Distance from the back of the cab to the centerline of the rear axle.



Truck shown with optional equipment.



Truck shown with optional equipment.



GVWR (lbs./kg)	33,000 / 14,950
Gross axle weight rating (GAWR) (lbs./kg)	Front 12,000 / 5,440 Rear 21,000 / 9,530
Engine (Hino)	J08E-VB Diesel, 6-cylinder, turbo intercooled, 7.7L DEF-SCR Dosing system
Exhaust gas aftertreatment system	
Max. Output (HP)	260 @ 2,500 rpm
Max. Torque (lb.-ft.)	660 @ 1,500 rpm
Transmission	6-speed Allison 2500 RDS
Fuel tank (ltr./gal.)	189 / 50, aluminum (standard)
Dual aluminum tank (ltr./gal.)	189 / 50 x 2 (optional) 340 / 90 (optional)
Service brakes*	Hydraulic disc front and rear
Wheels	22.5 inch x 8.25 inch, 10 stud disc
Tire size	11R22.5
Wheelbase/CA**	
WB	187.0 205.0 217.0 235.0 253.0 271.0 280.0
CA	119.6 137.6 149.6 167.6 185.6 203.6 212.6



Model 338

* 338 models are also available with air brakes. See dealer for details.
 ** See dealer for wheelbase availability
 WB: Distance between the centerline of the front and rear axles.
 CA: Distance from the back of the cab to the centerline of the rear axle.



GVWR (lbs./kg)	35,000 / 15,870
Gross axle weight rating (GAWR) (lbs./kg)	Front 13,200 / 5,990 Rear 23,000 / 10,430
Engine (Hino)	J08E-VB Diesel, 6-cylinder, turbo intercooled, 7.7L
Exhaust gas aftertreatment system	DEF-SCR Dosing system
Max. Output (HP)	260 @ 2,500 rpm
Max. Torque (lb.-ft.)	660 @ 1,500 rpm
Transmission	6-speed Allison 3000 RDS
Fuel tank (ltr./gal.)	189 / 50, aluminum (standard) 340 / 90, aluminum (optional)
Service brakes	Full air
Wheels	22.5 inch x 8.25 inch, 10 stud disc
Tire size	11R22.5
Wheelbase/CA*	
WB	187.0 205.0 217.0 235.0 253.0 271.0
CA	119.6 137.6 149.6 167.6 185.6 203.6



* See dealer for wheelbase availability
WB: Distance between the centerline of the front and rear axles.
CA: Distance from the back of the cab to the centerline of the rear axle.



Truck shown with optional equipment.

WARRANTY COVERAGE

Description

Months/ Mileage (km)

BASIC TRUCK COMPONENTS

Provides warranty protection against defects in material and workmanship for 24 months/ unlimited mileage. Includes towing* to nearest Hino Dealer for warrantable failures. (Adjustments and expendables such as bulbs and fuses are covered for 90 days/ 5,000 km. Batteries and radio are covered for 12 months).

**To a maximum of \$1000 per tow*

24 months/ Unlimited

ENGINE

Provides warranty protection against defects in material and workmanship for 60 months/ 400,000 km for all of the internal engine components plus the following: cylinder block, cylinder head, fuel supply pump, unit injectors, turbocharger and flywheel housing.

60 months/ 400,000km

EMISSIONS WARRANTY

Provides warranty protection against defects in material and workmanship for 60 months/ 160,000 km, whichever occurs first, for the emission control system.

60 months/ 160,000km

FRAME RAILS AND CROSS MEMBERS

Provides warranty protection against structural cracks in the frame and cross members caused by defects in material and workmanship for 60 months/ unlimited mileage.

60 months/ Unlimited

Conventional Model Trucks

Description

Months/ Mileage (km)

CAB

Provides warranty protection against corrosion perforation of the cab structure for 60 months/ unlimited mileage.

60 months/ Unlimited

AUTOMATIC TRANSMISSION: ALLISON 2000/3000 SERIES

Warranty covers repairs or replacement, at Allison Transmission's option, to correct any transmission malfunction resulting from defects in materials or workmanship for 36 months/ unlimited mileage. Allison Transmissions are warranted by Allison for the time and mileage specified.

36 months/ Unlimited

Transmission Options available for:

Hino Models 268 (with 253" and 271" wheelbase): Allison 2200HS Highway Series

Hino Models 338 (with 253", 271" & 280" wheelbase): Allison 2500HS Highway Series

Warranty covers repairs or replacement for an additional year, total 48 months/ unlimited mileage, to correct any transmission malfunction resulting from defects in materials or workmanship. Allison Transmissions are warranted by Allison for the time and mileage specified.

48 months/ Unlimited

ANTI-LOCK BRAKING SYSTEM (ABS) AIR/HYDRAULIC

Provides warranty protection against defects in material and workmanship for 36 months/ 480,000 km, whichever occurs first, for the following components: wheel sensors, modulator valves and ECU.

36 months/ 480,000km



HINO PREMIUM PROTECTION



HINO PREVENTIVE CARE

The Hino Preventive Care plan consists of the following items to protect your truck and enhance its longevity:

- 1 year scheduled maintenance, up to 50,000 kilometers
- Complimentary engine oil changes and chassis lubrication services for years 2 and 3, up to 150,000 kilometers; (Engine Oil, Transmission Fluid*, Differential Fluid and Chassis Lubrication)

** Applies to cab-over engine models only*



3 YEARS HINOWATCH ROADSIDE ASSISTANCE

HINOWATCH Roadside Assistance provides peace of mind driving since our customers know that assistance is only a toll-free phone call away. For the first 3 years of ownership, **HINOWATCH** protects your Hino truck with 24-hour roadside assistance at no extra charge. **HINOWATCH** covers the following: lockout service, out of fuel/DEF, battery jump-start and towing on warrantable repairs (up to a maximum of \$1,000 per tow).



5 YEAR WARRANTY

Protecting your investment, Hino provides quality products backed by a comprehensive warranty!

Hino's legendary **7.7 litre J08E engine** is covered by a **5 year/400,000 km** warranty on the conventional models. For the cab over engine models, the durable **5.1 litre J05E engine** and 6-speed automatic transmission are covered by a **5 year/320,000 km** warranty.

Any remaining balance of Hino's warranty is fully transferable to the new owner if you sell your vehicle, adding to its resale value.



HINO 3 YEAR PARTS WARRANTY

Introducing Hino's new **3 year, unlimited mileage warranty** on all Hino parts, installed at any Hino dealership across Canada. This new industry-leading warranty is another example of how we are dedicated to providing Hino Genuine Parts and committed to protecting your investment. A 1 year, unlimited mileage warranty applies for Hino parts sold over the counter.

Please contact your closest Hino dealership for further details.



HINO GENUINE PARTS

Hino Genuine Parts have been designed and tested to meet stringent quality control standards to ensure they provide the best value and performance for your Hino truck.



DISCLAIMER: All specifications of the products are with normal manufacturing allowances and tolerances. **HINO MOTORS CANADA, LTD.** reserves the right to discontinue items, or make changes at any time, without notice, to equipment, specifications, or materials.

Truck images courtesy of Hino Motors Sales U.S.A., Inc.

www.hinocanada.com



ISO 14001